

"A true multi-talent."

Blasogrind GTM 10



Elizabeth Fischer
Simon Stalder
R&D Chemist
Grinding Specialist
Blaser Swisslube AG

Our Liquid Tool. Your Success.

One grinding oil for all major cutting tool materials.

Blasogrind GTM 10

- Performance-optimized formulation
- Optimal cooling thanks to fast air release, preventing microcracks and allowing for smaller coolant tanks
- Good wetting and rinsing behavior for easy-to-clean workpieces and safe coating
- Colorless and transparent for a clear view of the grinding process
- Odorless for a pleasant working environment
- Good machine/polymer compatibility and filterability
- For individually filled machines and central systems

Best for grinding and re-grinding of cutting tools

- Can be used for a variety of materials such as carbide, HSS, steel and cermet
- Ensures high feed rates, long dressing intervals and excellent surface quality
- Also suitable for other grinding applications



High-speed steel HSS

No burn marks, minimal burrs

Tungsten carbide

No microcracks, no cobalt leaching

Product data

Viscosity at 40°C	10 mm ² /s
Flash point	195°C
Copper corrosivity	1a (3h at 60°C)
Color	Colorless (ASTM 0.5)

Note: Suitable for edge-type and pre-coat filters

Test us. It's worth it.

blaser.com/blasogrindgtm10



Our Liquid Tool. Your Success.